

MEGA LITE



NOVA-LITE_{VW150}

DESCRIPTION:

The Nova-Lite VW150 is a powerful LED fixture with an extremely wide coverage. The unit is equipped with a 150-watt single-source LED for a smooth, even output. It has a 55-degree reflector beam angle and ships with a 30-degree and 15-degree lens for longer throw applications. The unit is perfect for house light applications because it comes with a hanging adapter designed to fit a 1/2in all-thread or steel cable. The unit's connections include both 5-pin and 3-pin Neutrik XLR connections and Neutrik Power Conn in and out. A cable mounted Neutrik to Nema 5 15 is also included. Easily address and do stand alone programming on the unit's LCD display. For simple ground stacking and rigging, the fixture comes equipped with a double mounting yoke. Additionally, the Nova-Lite VW150 is ETL listed, making it certified for installation in more venues.

VERSATILE



MANY CONVENIENT
INSTALLATION OPTIONS

ETL LISTED



ETL CERTIFIED

POWERFUL



150 VARIABLE
WHITE LED

DMX CONTROL



6 MODES OF OPERATION



www.MEGASYSTEMSINC.COM | SALES@MEGASYSTEMSINC.COM | 866-460-MEGA (6342)

KEY FEATURES:

SPECIFICATIONS:

PART NUMBER:	4453-Nova Lite CW150
DMX CONNECTORS:	Neutrik 3 & 5 pin
POWER CONNECTION:	Neutrik Power Con to Nema 5-15 (Cable mounted)
THERMAL:	Maximum ambient temperature 105° Maximum surface temperature 113°
FASTENING SYSTEM:	Dual Yoke
DISPLAY	Digital
LENS ANGLES:	55° Reflector, 30° and 15° lens (Included) 60° and 80° Field angle diffusion lens (Accessory)
LED QUANTITY:	1
LED WATT:	150 Watts
LED LIFETIME:	40 to 80 thousand hours Average
REFRESH RATE:	12000 Hz
POWER INPUT VOLTAGE:	110V-240 5-/60 Hz
BALLAST:	Electronic Auto Switching
POWER CONSUMPTION:	.1.39 Amps / 163 Watts
PROTOCOL:	DMX 512
CONTROL OPTIONS:	Display preset setting
OPERATING MODE:	6 Modes of Channel operation

ACCESSORIES:

	PART NUMBER
60 DEGREE DIFFUSION LENS	4450-DIF60
CEILING TILE HOLDERS (SET)	4450-CT
BARN DOOR	4450-BD
HANGING POINT METRIC (10MM)	4450-HPM
DECORATIVE TRIM (CUSTOM COLOR)	4450-DT

PHOTOMETRICS:

WARM WHITE (At 10ft)	
CCT	3222 K
CRI	90.0
Lux	589.3
fc	54.8

COOL WHITE (At 10ft)	
CCT	6609 K
CRI	92.5
Lux	79425.0
fc	7381.5

WARM AND COOL WHITE (At 10ft)	
CCT	4179 K
CRI	97.1
Lux	126805.0
fc	11784.8

PHYSICAL SIZE:

Fixture

Size: 10.25" x 11.85" x 5.75"
Weight: 7 lb

Packaged for Shipping

Size: 13.5" x 11.25" x 7.5"
Weight: 8.75 lb

