

MEGA^{LITE}



NOVA-LITE_{T200}

DESCRIPTION:

The Nova-Lite T200 is a powerful color changing LED fixture with extremely wide coverage. The unit is equipped with a 200-watt single-source RGB LED for a smooth, even output. It has a 55-degree reflector beam angle and ships with a 30-degree and 15-degree lens for longer throw applications. A 60-degree diffuser accessory is available for softening the edge of the output. The unit is perfect for house light applications because it comes with a hanging adapter designed to fit a 1/2in all-thread or steel cable. The Nova-Lite T200 is controlled via DMX 512. It has 4 modes of operation and up to 7 channels including R,G,B, Strobe, Macro, Dim Speed. The unit's connections include both 5-pin and 3-pin Neutrik XLR connections and Neutrik Power Conn in and out. A cable mounted Neutrik to Nema 5 15 is also included. Easily address and do stand alone programming on the unit's blue LCD display. For simple ground stacking and rigging, the fixture comes equipped with a double mounting yoke. Additionally, the Nova-Lite T200 is ETL listed, making it certified for installation in more venues.

VERSATILE



MANY CONVENIENT
INSTALLATION OPTIONS

ETL LISTED



ETL CERTIFIED

POWERFUL



200 RGB LED

DMX CONTROL



6 MODES OF OPERATION



KEY FEATURES:

SPECIFICATIONS:

PART NUMBER:	4451-Nova Lite T200
DMX CONNECTORS:	Neutrik 3 & 5 pin
POWER CONNECTION:	Neutrik Power Con to Nema 5-15 (Cable mounted)
THERMAL:	Maximum ambient temperature 105° Maximum surface temperature 113°
FASTENING SYSTEM:	Dual Yoke
DISPLAY	Digital
LENS ANGLES:	55° Reflector, 30° and 15° lens (Included) 60° and 80° Field angle diffusion lens (Accessory)
LED QUANTITY:	1
LED WATT:	200 Watts
LED LIFETIME:	40 to 80 thousand hours Average
REFRESH RATE:	12000 Hz
POWER INPUT VOLTAGE:	110V-240 5-/60 Hz
BALLAST:	Electronic Auto Switching
POWER CONSUMPTION:	1.39 Amps / 163 Watts
PROTOCOL:	DMX 512
CONTROL OPTIONS:	Display preset setting
OPERATING MODE:	6 Modes of Channel operation

ACCESSORIES:

	PART NUMBER
60 DEGREE DIFFUSION LENS	4450-DIF60
CEILING TILE HOLDERS (SET)	4450-CT
BARN DOOR	4450-BD
HANGING POINT METRIC (10MM)	4450-HPM
DECORATIVE TRIM (CUSTOM COLOR)	4450-DT

PHYSICAL SIZE:

Fixture

Size: 10.25" x 8" x 16.87"
Weight: 10.25 lb

Packaged for Shipping

Size: 20" x 12" x 11"
Weight: 13 lb

