

# MEGA LITE



## NOVA-LITE<sub>WW150</sub>

### DESCRIPTION:

The Nova-Lite WW150 is a powerful warm white LED fixture with extremely wide coverage. The unit is equipped with a 150-watt single-source WW LED for a smooth, even output. It has a 55-degree reflector beam angle and ships with a 30-degree and 15-degree lens for longer throw applications. The unit is perfect for house light applications because it comes with a hanging adapter designed to fit a 1/2in all-thread or steel cable. The unit's connections include both 5-pin and 3-pin Neutrik XLR connections and Neutrik Power Conn in and out. A cable mounted Neutrik to Nema 5 15 is also included. Easily address and do stand alone programming on the unit's LCD display. For simple ground stacking and rigging, the fixture comes equipped with a double mounting yoke. Additionally, the Nova-Lite WW150 is ETL listed, making it certified for installation in more venues.

#### VERSATILE



MANY CONVENIENT  
INSTALLATION OPTIONS

#### ETL LISTED



ETL CERTIFIED

#### POWERFUL



150 WW LED

#### DMX CONTROL



8 MODES OF OPERATION



[www.MEGASYSTEMSINC.COM](http://www.MEGASYSTEMSINC.COM) | [SALES@MEGASYSTEMSINC.COM](mailto:SALES@MEGASYSTEMSINC.COM) | 866-460-MEGA (6342)

## KEY FEATURES:

### SPECIFICATIONS:

|                             |   |
|-----------------------------|---|
| <b>PART NUMBER:</b>         | 4452-Nova Lite WW150  |
| <b>DMX CONNECTORS:</b>      | Neutrik 3 & 5 pin   |
| <b>POWER CONNECTION:</b>    | Neutrik Power Con to Nema 5-15 (Cable mounted)  |
| <b>THERMAL:</b>             | Maximum ambient temperature 105°   Maximum surface temperature 113°                           |
| <b>FASTENING SYSTEM:</b>    | Dual Yoke   |
| <b>DISPLAY</b>              | Digital   |
| <b>LENS ANGLES:</b>         | 55° Reflector, 30° and 15° lens (Included) 60° and 80° Field angle diffusion lens (Accessory) |
| <b>LED QUANTITY:</b>        | 1   |
| <b>LED WATT:</b>            | 150 Watts   |
| <b>LED LIFETIME:</b>        | 40 to 80 thousand hours Average   |
| <b>REFRESH RATE:</b>        | 12000 Hz  |
| <b>POWER INPUT VOLTAGE:</b> | 110V-240 5-/60 Hz   |
| <b>BALLAST:</b>             | Electronic Auto Switching   |
| <b>POWER CONSUMPTION:</b>   | .1.39 Amps / 163 Watts  |
| <b>PROTOCOL:</b>            | DMX 512   |
| <b>CONTROL OPTIONS:</b>     | Display preset setting  |
| <b>OPERATING MODE:</b>      | 3 Modes of Channel operation  |

### ACCESSORIES:

|                                | PART NUMBER |
|--------------------------------|-------------|
| 60 DEGREE DIFFUSION LENS       | 4450-DIF60  |
| CEILING TILE HOLDERS (SET)     | 4450-CT     |
| BARN DOOR                      | 4450-BD     |
| HANGING POINT METRIC (10MM)    | 4450-HPM    |
| DECORATIVE TRIM (CUSTOM COLOR) | 4450-DT     |

### PHYSICAL SIZE:

#### Fixture

Size: 10.25" x 11.85" x 5.75"  
Weight: 7 lb

#### Packaged for Shipping

Size: 13.5" x 11.25" x 7.5"  
Weight: 8.75 lb

